

TECHNICAL DATA SHEET



Eurovent FAST

Liner-Free, high-performance, single-sided adhesive tape. Made of polyethylene film reinforced with polyester fiber and coated with a special acrylic dispersion adhesive, it offers exceptional adhesive strength, ensuring durable sealing even in demanding conditions. The key advantage of Eurovent® FAST is its liner-free design, which eliminates waste and enhances work safety during installation. Additionally, the serrated edge allows for quick and easy tearing of the tape without the need for tools.

PARAMETER	UNIT	VALUE
Material composition		PE film reinforced with a mesh, acrylic dispersion-based adhesive, solvent-free, EC1.
Width	[mm]	60
Length	[m]	25
Thickness	[mm]	0,24 - 0,26
Tensile strength	[N/25 mm]	≥30
Elongation	[N/25 mm]	≥35; 60%
Application temperature	[°C]	Recommended +5°C
Temperature resistance	[°C]	-30 up to +100
Adhesion strength		Very high
Resistance to water vapor		Very high
Aging resistance		Very high
UV resistance		Resistant
Packaging	[roll]	10
Pallet	[box/rolls]	60 / 600
Storage		In dry areas, in the original packaging



Eurovent **FAST**

Application: Designed for bonding and repairing vapor control layers, roof membranes and housewraps, as well as joining them with polypropylene- and polyethylene-based materials, insulation-reinforced papers, wood, metal elements, plasterboard, and stone. It provides excellent adhesion and sealing for curved surfaces and is recommended for sealing installation penetrations through vapor control membranes. It is also highly effective for repairing various damages such as holes, cuts, or installation tears. Eurovent[®] FAST is liner-free, eliminating waste and increasing work safety during installation. The serrated edge enables quick and convenient tearing of the tape without tools. Recommended for bonding and repairing vapor control membranes in traditional, timber-frame, and modular construction.

Montage:

Installation can be carried out without tools – the serrated edge allows for quick and convenient tearing of the tape. The application area must be structurally sound, dry, and free of dust or grease. Prior to bonding, the surfaces should be thoroughly cleaned, and an adhesion test should be performed. Finished connections should not be exposed to standing water or constant mechanical load. Any wrinkles or tension in the tapes must be smoothed out.

Safety: This product is not intended for consumption. Avoid contact with eyes, and if skin irritation occurs, consult a doctor.

Storage / transport: The product should be stored at temperatures ranging from +10°C to +30°C in a dry place, under cover, free from moisture and UV radiation, in its original undamaged and sealed packaging. The product should be transported in covered vehicles, protected from damage and destruction. During transport, all safety regulations must be observed. The product should be protected from chemical agents, particularly solvent-based substances, as they can reduce its technical parameters or cause permanent damage.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 02/04/2025