

## Eurovent **FIX TUBE GERMANIA**

The adapter for snow-stopping pipe Eurovent FIX TUBE GERMANIA is designed for use as an adapter for snow-stopping pipe. Designed for use as a protection element enabling efficient installation of the snow-stopping pipe on sloping roofs covered with profiled GERMANIA SIMETRIC 350/30 mm-module metal roofing tiles. Its installation is quick and easy - it is fixed directly to the roof construction with the use of screws.



| PARAMETER             | UNIT  | VALUE  |
|-----------------------|-------|--|
| Material              |       | Steel (grade S235JR)   |
| Dimension             | [mm]  | Flat bar 30  |
| Bracket length        | [mm]  | 350  |
| Fin height            | [mm]  | About 180  |
| Steel sheet thickness | [mm]  | Flat bar - 4 mm<br>Fin - 3 mm  |
| Hole diameter         | [mm]  | Ø 34   |
| Hole spacing          | [mm]  | 47   |
| Colour                | [RAL] | Galvanized steel; wallred 8004; brown 8017; brown 8019; anthracite 7016; graphit 7024; black 9005; cherry 3004; chestnut 3009; cherry 3011 |
| Corrosion protection  |       | Hot-dip galvanized   |
| UV resistance         |       | Resistant  |
| Package               | [pcs] | 10   |

### Advantages:

- Double protection against corrosion
  - Fast and easy installation
- For GERMANIA SIMETRIC 350/30mm-module metal roofing tile

## Eurovent **FIX TUBE GERMANIA**

### Application:

The adapter for snow-stopping pipe Eurovent FIX TUBE GERMANIA is designed for use as an adapter for snow-stopping pipe. Designed for use as a protection element enabling efficient installation of the snow-stopping pipe on sloping roofs covered with profiled GERMANIA SIMETRIC 350/30 mm-module metal roofing tiles. Its installation is quick and easy - it is fixed directly to the roof construction with the use of screws.

| ADAPTER           | THE LENGTH OF THE ROOF TILE MODULE [MM] | HEIGHT OF CREASE [MM] |
|-------------------|---|-----------------------|
| FIX TUBE GERMANIA | 350                                     | 30                    |

### Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

*Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Data aktualizacji: 02/2021