

Eurovent **PRIMER**

High-performance primer spray. It is used as a primer before applying adhesive tapes, seals on loose, absorbent, fibrous, sandy surfaces, and others with poor adhesion. It is characterized by high efficiency, fast drying, intense bonding with the substrate, and aging resistance. The rotating nozzle tip facilitates application. For use outdoors and indoors in well-ventilated areas.



PARAMETER	UNIT	VALUE
Material		Synthetic rubber
Color		Colorless
Capacity	[ml]	500
Application temperature	[°C]	from -10 to +30
Temperature resistance	[°C]	from -20 to + 80
Shelf life	[miesiący]	Min. 12
Waste management		Do not dispose of in household waste.
Packaging	[pcs]	12
Pallet	[pcs]	1008

Advantages:

- Fast and easy application
- Colorless
- Extremely enhances the adhesion of sealing tapes

Eurovent PRIMER

Application:

To ensure effective bonding, make sure the surface is firm, dry, clean, and free of dust and grease. Compatibility tests of the materials being joined are required. Apply PRIMER evenly onto the substrate, holding the can at least 20 cm away from the surface. Depending on the material used, please ventilate for 5-15 minutes. Repeat this process for highly absorbent surfaces. Protect sprayed surfaces from moisture, dust, and contaminants. After each spraying procedure, turn the can upside down and continue spraying until only the propellant is released. This prevents clogging of the spray nozzle with adhesive residues. Clean any adhesive residue from the discharge nozzle. The valve can be adjusted to three different levels. The spray nozzle can also be adjusted between horizontal and vertical spray patterns.



Eurovent PRIMER

Safety:

Extremely flammable aerosol. Pressurized container. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames. Do not expose to temperatures exceeding 50°C. Do not spray towards open flame or other ignition sources. Do not pierce or burn, even after use. Do not inhale aerosol. Use only outdoors or in well-ventilated areas. Product causes serious eye irritation. May cause drowsiness and dizziness. Harmful to aquatic life with long-lasting effects. In case of ingestion or contact with eyes, seek medical advice immediately, avoid direct contact with skin. When using, it is necessary to wear solvent-resistant gloves and safety goggles.

Storage / transport

The product should be stored at a temperature between +5°C to +25°C, in original packaging, in dry, covered rooms free from moisture. It is not recommended to stack the product with other heavy items (both during transport and storage). It should be transported in covered vehicles, protected from damage. Safety transport regulations must be followed during transportation. The product should be protected from the action of chemicals that could reduce its technical parameters or permanently damage it. The storage period in sealed packaging is 12 months from the date of production.

The product is covered by a warranty provided that the guidelines contained in the technical data sheet are strictly followed. The manufacturer reserves the right to refuse to acknowledge claims if the guidelines are not followed.

The information, recommendations, and guidelines provided are based on our best knowledge, research, experience, and good faith. We do not accept responsibility for the consequences of incorrect or erroneous use of our products. Each user of this material will ensure in every possible way, including testing the final product under appropriate conditions, the suitability of the materials provided to achieve their intended goals.

Product information is available on the website: www.eurovent.pl

Update date: 07/2024