



EN 13859-1:2010; EN 13859-2:2010  
**Declaration of Performance**

According to Annex of Regulation (EU) No. 305/2011  
Nr DoP 1-23042024-14-SA  
FOR THE PRODUCT

**PREMIUM PRIVATE LABEL 280 SA / Eurovent SUPER SA**

1. Product type: unique identification code of the product type	1-23042024-14-SA
2. Intended use or uses of the construction product	Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane
3. Manufacturer	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Poland VAT PL 9372516153
4. Authorized representative	Not relevant
5. System or systems of assessment and verification of constancy of performance	System 3
6. Harmonized specification(s). Notified body(ies).	EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous roofing EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799

7. Declared performance

CHARACTERISTIC	HARMONIZED TECHNICAL SPECIFICATION	VALUES
Reaction to fire	EN 13859-1:2010; EN 13859-2:2010	E
Resistance to water penetration	EN 13859-1:2010; EN 13859-2:2010	W1
Tensile strength MD	EN 13859-1:2010; EN 13859-2:2010	≥375 N/50 mm (+/- 90 N/50 mm)
Tensile strength CD	EN 13859-1:2010; EN 13859-2:2010	≥250 N/50 mm (+/- 80 N/50 mm)
Elongation MD	EN 13859-1:2010; EN 13859-2:2010	≤60%
Elongation CD	EN 13859-1:2010; EN 13859-2:2010	≤60%
Tearing Resistance MD	EN 13859-1:2010; EN 13859-2:2010	≥200 N (+/-30 N)
Tearing Resistance CD	EN 13859-1:2010; EN 13859-2:2010	≥210 N (+/-35 N)
Flexibility at low temperatures	EN 13859-1:2010; EN 13859-2:2010	w -30 °C comforming
Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat		
Resistance to water penetration	EN 13859-1:2010; EN 13859-2:2010	W1
Tensile strength MD change	EN 13859-1:2010; EN 13859-2:2010	<30%
Tensile strength CD change	EN 13859-1:2010; EN 13859-2:2010	<30%
Elongation MD change	EN 13859-1:2010; EN 13859-2:2010	≤60%
Elongation CD change	EN 13859-1:2010; EN 13859-2:2010	≤60%
Water vapor transmission	EN 13859-1:2010; EN 13859-2:2010	Sd <0,1m (+0,3 m)
Hazardous substances	EN 13859-1:2010; EN 13859-2:2010	Does not contain

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 305/2011 under the sole responsibility of the manufacturer specified in this declaration.

**Marcin Świerta**  
President



Przywory, 02.09.2024 r.