

Eurovent SNOWSTOP DC-3

The snowstopper used as an element to break up large amounts of snow sliding down from the roof slope towards the eaves. Made entirely of galvanized steel, painted with polyester paint on both sides. It is available in several colours according to the RAL palette. Dedicated to a specific group of roofing manufacturers.



PARAMETER	UNIT	VALUE
Material		Steel plate
Coverage Type		For tiles: (Tondach) Francuska 12, Falcovka, Marsylka 12; (Ruup) Rubin; (Creaton) Domino, Ratio Neu, Piatta; (Brass) Amber 12V; (Koramic) Alegra 89; (Bogen) Innovo 12;
Steel sheet thickness	[mm]	1,20 - 1,5 (±0,20)
Corrosivity category	[standard system 4]	C1; C2; C3;
Strength	[kN]	Min. 0,75
UV resistance		Resistant
Colour	[RAL]	Wallred 8004; brown 8017; chestnut 8012; black 9005; anthracite 7016
Package	[pcs]	100
Pallet	[pcs]	3 000

Advantages:

- Fast and easy installation
- Strong and durable
- Resistant to ageing processes

Eurovent SNOWSTOP DC-3

Application and installation:

The snowstopper used on sloping roofs as an element breaking snow - a snowstopper. It is fixed by an additional batten or by single roof tiles with a specially profiled ending. Thanks to its use, large amounts of snow sliding down from the roof are broken down into smaller pieces, therefore they do not pose a threat to people in the neighbourhood of the building.

Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.

Product information can be found on the website: www.eurovent.de

Data aktualizacji: 05/2020