



EN 13859-1:2010; EN 13859-2:2010  
**Declaration of Performance**

According to Annex of Regulation (EU) No. 305/2011  
Nr DoP 1-14022024-08  
for the product

**PREMIUM PRIVATE LABEL 140 / Eurovent MAXI**

|   |  |
|---|--|
| 1. Product type: unique identification code of the product type                 | 1-14022024-08  |
| 2. Intended use or uses of the construction product                             | Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane  |
| 3. Manufacturer   | Eurosystem Polska Sp. z o.o. Sp. K.<br>Wiejska 13, 46-055 Przywory, Poland<br>VAT PL 9372516153  |
| 4. Authorized representative  | Not relevant   |
| 5. System or systems of assessment and verification of constancy of performance | System 3   |
| 6. Harmonized specification(s). Notified body(ies).                             | EN 13859-1:2010 Flexible sheets for waterproofing<br>– Definitions and characteristics of underlays<br>– Part 1: Underlays for discontinuous roofing<br>EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls<br>Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799. |

7. Declared performance

| CHARACTERISTIC   | HARMONIZED TECHNICAL SPECIFICATION | VALUES                           |
|--|------------------------------------|----------------------------------|
| Reaction to fire   | EN 13859-1:2010; EN 13859-2:2010   | E                                |
| Resistance to water penetration  | EN 13859-1:2010; EN 13859-2:2010   | W1                               |
| Tensile strength MD  | EN 13859-1:2010; EN 13859-2:2010   | ≥300 N/50 mm<br>(+/- 85 N/50 mm) |
| Tensile strength CD  | EN 13859-1:2010; EN 13859-2:2010   | ≥210 N/50 mm<br>(+/- 80 N/50 mm) |
| Elongation MD  | EN 13859-1:2010; EN 13859-2:2010   | ≤60%                             |
| Elongation CD  | EN 13859-1:2010; EN 13859-2:2010   | ≤60%                             |
| Tearing Resistance MD  | EN 13859-1:2010; EN 13859-2:2010   | ≥160 N (+/-40N)                  |
| Tearing Resistance CD  | EN 13859-1:2010; EN 13859-2:2010   | ≥150 N (+/-35N)                  |
| Flexibility at low temperatures  | EN 13859-1:2010; EN 13859-2:2010   | w -30 °C<br>comforming           |
| Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat |                                    |                                  |
| Resistance to water penetration  | EN 13859-1:2010; EN 13859-2:2010   | W1                               |
| Tensile strength MD change   | EN 13859-1:2010; EN 13859-2:2010   | <30%                             |
| Tensile strength CD change   | EN 13859-1:2010; EN 13859-2:2010   | <30%                             |
| Elongation MD change   | EN 13859-1:2010; EN 13859-2:2010   | ≤60%                             |
| Elongation CD change   | EN 13859-1:2010; EN 13859-2:2010   | ≤60%                             |
| Water vapor transmission   | EN 13859-1:2010; EN 13859-2:2010   | Sd = 0,02 m (+/-0,019 m)         |
| Hazardous substances   | EN 13859-1:2010; EN 13859-2:2010   | Does not contain                 |

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 305/2011 under the sole responsibility of the manufacturer specified in this declaration.

**Marcin Świerta**  
President



Przywory, 14.02.2024 r.