

## Eurovent **STEP SET METAL 350**

The Eurovent STEP SET METAL 350 is a chimney step in a complete assembly set consisting of the Eurovent® SUPPORT METAL 350 adapter and the Eurovent® STEP chimney step. The elements made of galvanized steel form a complete system for safe traffic on the roof slope with an angle of 15° to 60°. The product features anti-slip corrugations on the whole surface and a hand grip. The set is available in several colour versions painted with powder paint according to RAL chart.



PARAMETER	UNIT	VALUE
Material		Steel grade S235JR
Coverage Type		350 module roofing tiles
Step dimension	[mm]	About 170 x 256
Strength of elements	[norm]	EN 516:2007
Non-slip surface		YES
Corrosion protection		Hot-dip galvanized
UV resistance		Resistance
Colour	[RAL]	Galvanized steel; wallred 8004; brown 8017; brown 8019; anthracite 7016; anthracite 7024*; black 9005; red 3004; green 6020*; cherry: 30011*
Packaging Weight	[kg]	ca. 5
Package	[pcs]	1 STEP + 1 SUPPORT METAL 350 + 2 screws

### Advantages:

- Ready-to-install set
- Double anti-corrosion protection
- For profiled metal roof coverings  
- 350° module roofing tiles

\* to order

## Eurovent **STEP SET METAL 350**

### Application:

The Eurovent STEP SET METAL 350 chimney step is used as a roof communication element that enables safe foot traffic of a chimney sweeper on the chimney area. The set consists of 2 complete steps and includes all the elements needed to install two chimney steps. Due to the wide range of adapters, the product can be adjusted to almost any type of roofing. It is recommended to install it on roof slopes with an angle of 15° to 60°.

### Fitting:

The step is fixed to the roof covering i.e. metal roof as well as to the batten by means of screws.

### Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

*Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Data aktualizacji: 04/2020