

Eurovent VISTA DUO

The roof exit Eurovent VISTA is made of vacuum impregnated pine wood. Product features a double 15 mm pane mounted on aluminum profile. Installed as part of the roof of roof access system to allow safe foot traffic and efficient maintenance works. Integrated flashing ensures fast and easy installation on flat, corrugated and high-profile roof coverings. It has two ventilation positions and a pre-mounted upward or lateral opening system, which can be set according to preference. Suitable for attics and roof ranging in slope from 15 to 60 degrees.



PARAMETER	UNIT	VALUE
Material		Pinewood, aluminum sheet; glass
Dimensions	[cm]	45 x 55; 45 x 73; 48 x 90;
Colour	[RAL]	Gray
Glass type		Double
UV-resistant		Resistant
Box	[pcs]	1
Pallet	[pcs]	48 cm x 90 cm- 10 pcs.; other 11 psc.

Advantages:

- Equipped with one integrated flashing
 - Fast and easy installation
 - Tilt up and to the side

Eurovent VISTA DUO

Application:

The roof exit Eurovent VISTA is used in ventilated sloping roofs with an attic as an element of roof communication for chimney sweepers, roofers and installers. Designed to enable periodic roof inspections, roof maintenance works as well as evacuation from the attic to the roof. Provides additional light and enables proper ventilation of the attic space in a sloping roof. Special hinge allows to tilt and latch the casement in two positions, which guarantee effective ventilation of the attic. Integrated flashing allows for installation with all types of roof coverings.



Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.

Product information can be found on the website: www.eurovent.de

Data aktualizacji: 07/2020