


TECHNICAL DATA SHEET

Eurovent DIFFUBAND SK2

Sealing tape with low Sd coefficient for insulation of the connection for the outside. Made of highly vapour-permeable membrane fully coated with an adhesive layer on one side and an adhesive strip on the other side that provides optimal performance and makes plastering and final processing easier.



PARAMETRER	UNIT	VALUE
Carrier Material	[°C]	1 layer pp nonwoven
Available widths	[mmx rm]	70, 100, 150 x 25
Water tightness		W1
Vapour permeability	[Sd]	0,3 (±0,02)
Flammability class		E
Adhesive		Acrylate dispersion, solvent free EC1 ^{PLUS}
Adhesive Coating	[g/m ²]	230
Temperature resistance	[°C]	-40 to +80
UV Resistance	[months]	4
Shelf life		1 year
Package	BOX(pallet)	8 rolls (384); 6 rolls (288); 1 roll (240)
Storage		In a dry place at a temperature of + 15 °C to + 25°C


Advantages:

- Vapour insulating • flexible and easy to install
- Wind insulation • Allows moisture drainage from joints
- Very low emission EMICODE® EC1^{PLUS}

Eurovent DIFFUBAND SK2

Application:

For the installation of windows and doors in a way that ensures their tightness for many years. Dedicated for the insulation of connections outside the building. The product is self-adhesive on the entire surface which makes easy installation of the foil. Additionally, it contains an adhesive stripe on the top side which facilitates fastening of the tape to the wall and eliminates the need of using additional adhesive.



Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.

The information on the product is included on the website: www.eurovent.de

Date of update: 04/2020