



Declaration of Performance

According to Annex of Regulation (EU) No. 305/2011
Nr DoP 1-12072024-03
for the product

Eurovent **MAXI PLUS**

1. Product type: unique identification code of the product type	1-12072024-03
2. Intended use or uses of the construction product	Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane
3. Manufacturer	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Poland VAT PL 9372516153
4. Authorized representative	Not relevant
5. System or systems of assessment and verification of constancy of performance	System 3
6. Harmonized specification(s). Notified body(ies).	EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous roofing EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls BTTG HIGH PERFORMANCE MATERIALS Unit 14, Wheel Forge Way, Trafford Park Manchester, M17 1EH, England, Test report: 11/18799/B1/PJH

7. Declared performance

CHARACTERISTIC	HARMONIZED TECHNICAL SPECIFICATION	VALUES
Reaction to fire	EN 13859-1:2010; EN 13859-2:2010	E
Resistance to water penetration	EN 13859-1:2010; EN 13859-2:2010	W1
Tensile strength MD	EN 13859-1:2010; EN 13859-2:2010	≥300 N/50 mm (±40 N/50 mm)
Tensile strength CD	EN 13859-1:2010; EN 13859-2:2010	≥220 N/50 mm (±20 N/50 mm)
Elongation MD	EN 13859-1:2010; EN 13859-2:2010	50-85 %
Elongation CD	EN 13859-1:2010; EN 13859-2:2010	90-130 %
Tearing Resistance MD	EN 13859-1:2010; EN 13859-2:2010	190 N (±35 N)
Tearing Resistance CD	EN 13859-1:2010; EN 13859-2:2010	200 N (±50 N)
Flexibility at low temperatures	EN 13859-1:2010; EN 13859-2:2010	w -40 °C comforming
Water vapor transmission	EN 13859-1:2010; EN 13859-2:2010	0,02 m (±0,019)

Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat

Resistance to water penetration	EN 13859-1:2010; EN 13859-2:2010	W1
Tensile strength MD change	EN 13859-1:2010; EN 13859-2:2010	280 N/50mm (±40 N/50mm)
Tensile strength CD change	EN 13859-1:2010; EN 13859-2:2010	185 N/50mm (±30 N/50mm)
Elongation MD change	EN 13859-1:2010; EN 13859-2:2010	≥65% of the initial value
Elongation CD change	EN 13859-1:2010; EN 13859-2:2010	≥65% of the initial value

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 305/2011 under the sole responsibility of the manufacturer specified in this declaration.

Marcin Świerta
President



Przywory, 23.04.2025 r.