

## TECHNICAL DATA SHEET

### Eurovent **VALLEY L**

Roof valley made of longitudinally pressed aluminum sheet and coated with polyester paint. Designed for use as flashing element between two neighbouring roof slopes. Ensures proper drainage of water from the roof.



PARAMETER	UNIT	VALUE
Material		aluminum sheet
UV resistance		resistant
Size	[mm x mb]	500 x 2
Weight	[kg]	ca. 1.5
Box	[pcs]	10

#### Advantages:

- Weatherproof
- Fast and easy installation
- Neat finishing

## Eurovent **VALLEY Q**

### Application:

Roof valley designed for use as flashing element to ensure proper water drainage from the roof. Installed between the neighbouring roof slopes. Shape and dimensions enable fast and easy application. Suitable for use with majority of roof coverings available on the market.



### Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent based substances, as they can reduce technical parameters of foil or permanently damage it.

*Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 01/2020