



### **TECHNICAL DATA SHEET**

#### **Eurovent FIX 21 METAL FINNERA**

The Eurovent FIX 21 METAL FINNERA is an adapter for snow-stopping grate. Manufactured from galvanized steel and The joints are thermally welded together. Designed for use as a mounting element for snow-stopping grate on a metal roof tile of the FINNERA module. Available in several colour versions painted with powder paint according to RAL chart. Suitable for application on roof slopes ranging from 15 to 60 degrees.



PARAMETER	UNIT	VALUE
Material		steel grade S235JR
Coverage Type		For profiled roof tiles
Coating thickness	[µm]	≥ 60
Corrosion protection		Hot-dip galvanized
Zinc coating thickness	[µm]	≥ 55
Colour	[RAL]	Galvanized steel; cherry 3004; cherry 3011; chestnut 3009; wallred 8004; brown 8017; brown 8019; anthracite 7016; graphite 7024, black 9005;
Package	[pcs]	10

# Advantages:

- Double protection against corrosion
- For metal roof tiles of the FINNERA module
  - Fast and easy installation





#### Furovent FIX 21 MFTAL FINNERA

## Application:

The adapter for snow-stopping grate Eurovent FIX 21 METAL FINNERA is designed for use as an adapter for snow-stopping grate. It is used as a protection element enabling efficient fixing of the snow-stopping grate on sloping roofs covered with profiled metal roof tiles of the FINNERA module. Its installation is quick and easy - it is fixed directly to the roof construction with the use of screws.

ADAPTER	MODULE LENGTH ROOFING SHEET "M" [mm]	HEIGHT OF CREASE "H" [mm]
FIX METAL FINNERA	331	30

#### Montage:

The step is fixed to the roof covering i.e. metal roof as well as to the batten by means of screws.

## Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.

Product information can be found on the website: www.eurovent.de

Data aktualizacji: 05/2021