



## **TECHNICIAL DATA SHEET**

#### **Eurovent STEP**

The Eurovent STEP is manufactured from galvanized steel. Designed to enable safe foot traffic on the roof slope with an angle of  $15^{\circ}$  to  $60^{\circ}$ . The product features anti-slip corrugations on the whole surface, mounted on the roof in conjunction with the adapter. Available in several colour versions painted with powder paint according to RAL chart.



PARAMETER	UNIT	VALUE
Material		Steel grade S235JR
Dimensions	[mm]	About 170 x 256
Construction requirements	[norm]	EN 516 : 2007
Coating thickness	[µm]	≥ 60
Non-slip surface		YES
Corrosion protection		Hot-dip galvanized
Zinc coating thickness	[µm]	≥ 55
Colour	[RAL]	Galvanized steel; wallred 8004; brown 8017; brown 8019; anthracite 7016; graphit 7024; black 9005; cherry 3004; chestnut 3009; cherry 3011
Package	[pcs]	10

# Advantages:

- Protection against corrosion
  - Fast and easy installation
- Universal solution for various roof coverings

<sup>\*</sup> to order





### **Eurovent STEP**

# Application:

The Eurovent STEP is designed as an element of roof communication to enable efficient foot traffic of a chimney sweeper on the chimney area as well as on the roof slope. Depending on the type of roofing, it is fixed on the roof with the use of a suitable adapter Eurovent® SUPPORT. The individual elements are joined together with special screws attached to the products.

### Fitting:

Mounted on the roofing depending on the type of roofing with the appropriate one Eurovent® SUPPORT bracket. Individual elements are joined together with screws. Thanks to her two-element construction allows you to adjust the angle of inclination of the degree depending on the amount of roof pitch.

### Storage / transport:

The product should be stored under roof in dry, damp-free rooms, protected from direct UV radiation. Product can be deformed, disfigured or suffer from damages of galvanized/paint coating if put under high pressure. Therefore it is unadvised to stack the product with other heavy products (both in storage and in transport). It is recommended to transport the product with use of covered means of transport, in manner that protects them from damage. During the transport safety regulations have to be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of the product or permanently damage it.

The product is under warranty, providing that the guidelines included in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

Included information, advices and guidance is given based on our best knowledge, researches, experience and in good faith. We are not be held responsible for the consequences of improper or incorrect use of our products. Each user of the product shall ensure, in every possible way, including checking the end-product in given conditions, that the provided product is suitable to reach objectives he pursues.

Product information can be found on the website: www.eurovent.de

Data aktualizacji: 02/2021