



EN 13859-1:2010; EN 13859-2:2010
Declaration of Performance

According to Annex of Regulation (EU) No. 305/2011
Nr DoP 1-12092024-86
FOR THE PRODUCT

PREMIUM PRIVATE LABEL 180 / Eurovent SUPER

| | |
|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Product type: unique identification code of the product type | 1-12092024-86 |
| 2. Intended use or uses of the construction product | Underlay for discontinuous roofing and as underlay for walls (roof underlay, vapour permeable, watertight, for the pitched roofing also fully sheathed, and as housewrap or fasade membrane |
| 3. Manufacturer | Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Poland VAT PL 9372516153 |
| 4. Authorized representative | Not relevant |
| 5. System or systems of assessment and verification of constancy of performance | System 3 |
| 6. Harmonized specification(s). Notified body(ies). | EN 13859-1:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous roofing EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799 |

7. Declared performance

| CHARACTERISTIC | HARMONIZED TECHNICAL SPECIFICATION | VALUES |
|--------------------------------------------------------------------------------------------------------------|------------------------------------|----------------------------------|
| Reaction to fire | EN 13859-1:2010; EN 13859-2:2010 | E |
| Resistance to water penetration | EN 13859-1:2010; EN 13859-2:2010 | W1 |
| Tensile strength MD | EN 13859-1:2010; EN 13859-2:2010 | ≥380 N/50 mm (+/- 90 N/50 mm) |
| Tensile strength CD | EN 13859-1:2010; EN 13859-2:2010 | ≥250 N/50 mm (+/- 80 N/50 mm) |
| Elongation MD | EN 13859-1:2010; EN 13859-2:2010 | ≤60% |
| Elongation CD | EN 13859-1:2010; EN 13859-2:2010 | ≤60% |
| Tearing Resistance MD | EN 13859-1:2010; EN 13859-2:2010 | ≥200 N (+/-30 N) |
| Tearing Resistance CD | EN 13859-1:2010; EN 13859-2:2010 | ≥210 N (+/-35 N) |
| Flexibility at low temperatures | EN 13859-1:2010; EN 13859-2:2010 | w -30 °C comforming |
| Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat | | |
| Resistance to water penetration | EN 13859-1:2010; EN 13859-2:2010 | W1 |
| Tensile strength MD change | EN 13859-1:2010; EN 13859-2:2010 | <30% |
| Tensile strength CD change | EN 13859-1:2010; EN 13859-2:2010 | <30% |
| Elongation MD change | EN 13859-1:2010; EN 13859-2:2010 | ≤60% |
| Elongation CD change | EN 13859-1:2010; EN 13859-2:2010 | ≤60% |
| Water vapor transmission | EN 13859-1:2010; EN 13859-2:2010 | Sd = 0,02 m (+/-0,019 m) |
| Hazardous substances | EN 13859-1:2010; EN 13859-2:2010 | Does not contain |

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 305/2011 under the sole responsibility of the manufacturer specified in this declaration.

Marcin Świerta
President



Przywory, 12.09.2024