


TECHNICAL DATA SHEET

Eurovent **CLIP J-2**

Double side-clip designed for fastening clay roof tiles. Made of J-shaped galvanized steel wire ensures fast and durable installation of the roof tile to the roof construction. Available in two sizes 300 mm and 320 mm.



PARAMETER	UNIT	VALUE
Material		galvanized steel
UV resistance		resistant
Size	[mm x mb]	300 x 15 x 15 mm; 320 x 15 x 15 mm
Colour		steel
Box weight	[kg]	1,5
Box	[pcs]	100

Advantages:

- Fast and easy application
- Protection against shifting
 - Reliable installation

Eurovent CLIP J-2

Application:

Roof tile designed for fastening clay tiles. Fixed by fastening its tips to the side-locks of two neighboring roof tiles, the upper and the lower one. Depending on the size of the roof tile, two lengths are available for application – 300 mm and 320 mm. Clip ensures reliable installation and helps to resist shifting of roof tiles caused by strong winds and wind suction.



Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent based substances, as they can reduce technical parameters of foil or permanently damage it.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2020