



16

Declaration of Performance

Nr DWU-GEO 8 S

Fundament foil Eurovent **GEO 8 S**

1. Unique identification code of the product type	GEO 8 S
2. Intended use or uses	For drainage and insulating systems and as a vapor barrier for anti-damp elements of underground ventilation. For sealing ditches and reservoirs, as the cut-off and insulating layer under roads and railroads, protective layer in roofs with reverse insulation system. Type V, Type T
3. Manufacturer	Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13 46-055 Przywory, Poland VAT PL9372516153
4. System of AVCP	System 2+
5. Notified body/ies	PN-EN 13967:2012 Notified certification body: Instytut Techniki Budowlanej, Warszawa, RP (Identification No 1488).

6. Declared performance

ESSENTIAL CHARACTERISTICS	USEFUL PROPERTIES	TESTING METHOD
Watertightness	Watertight at 2kPa	EN 1928:2002 (2k Pa)
Watertightness after artificial ageing	Watertight at 2kPa	EN 1928:2002 after test EN 1296 (70 °C/ 7 dni.)
Watertightness after exposure to chemicals	Watertight at 2kPa	EN 1847 (23°C/ 7 days EN 1928:2002 after test EN 1847 (23°C/ 7 days))
Tear resistance	MD ≥ 250N CMD ≥ 300N	EN 12310-1 : 2002 EN 12310-1 : 2002
Joint strength	NPD	EN 12317-2
Impact resistance	NPD	EN 12691
Reaction to fire	Class F	EN 13501-1
Maximum stretching strength	MD ≥ 250N/50mm CMD ≥ 220N/50mm	EN 12311 -2:2013
Resistance to static load	NPD	EN 12730

Product does not contain hazardous substances according with REACH regulation.

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

Marcin Świerta
President



Przywory, 04.11.2016 r.