

TECHNICAL DATA SHEET



Eurovent MULTI

Highly adhesive, solvent-free general-purpose adhesive, ideal for bonding vapour control layers, roofing membranes and films both inside and outside buildings. It offers excellent ageing resistance, is extremely flexible and stretchable, and accommodates building movements – suitable for expansion joint bonding. The adhesive can be plastered over and painted. Application should be carried out in a well-ventilated area, and once the sealant dries (approximately 12–24 hours), any odour will dissipate.

PARAMETER	UNIT	VALUE
Material		Solvent-free acrylic emulsion
Consistency		Pasty
pH value		Alkaline (7,8 – 8,2)
Application temperature	[°C]	-10 to +40
Temperature resistance	[°C]	-20 to + 80
Density	[kg/l]	1,02
Coverage	[mb]	8-10
Cardridge capacity	[g]	320
Color		Blue
Packaging	[pcs.]	20
Storage temperature	[°C]	+5°C up to +25°C
Pallet	[cartridges / pcs.]	60 / 1200



TECHNICAL DATA SHEET

Eurovent MULTI

Application: For bonding vapour barriers, roof membranes, and films both indoors and outdoors, including expansion joint applications. The adhesive is suitable for plastering and painting over. Application temperature min./max.: -10 °C to +40 °C. The surfaces to be bonded must be clean, degreased, and absorbent. On weak, dusty, or fibrous surfaces, a suitable primer should be used. The applied adhesive layer should be approximately 6 to 8 mm thick. Before curing, the adhesive can be easily removed with water. Once cured, any adhesive residue can be removed using cleaning agents by locally soaking the dried material. If necessary, the procedure should be repeated until the desired result is achieved. Make sure in advance that the surfaces from which the residue is being removed are resistant to the selected cleaning agent. Application should be carried out in a well-ventilated area; once cured (approx. 12–24 hours), any odour will disappear.

Safety: The product must be kept out of reach of children. In case of ingestion or contact with eyes, seek medical advice immediately. Avoid direct contact with skin. Protective gloves and safety goggles are recommended during use.

Storage / transport: The product should be stored at a temperature between +5 °C and +25 °C, in original packaging, in dry, covered, and moisture-free indoor areas. Adhesive cartridges may become deformed under excessive weight; therefore, stacking with other heavy products is not recommended during transport or storage. Transport must be carried out using covered vehicles, with the product properly secured against damage. All applicable transport safety regulations must be followed. The product should be protected from exposure to chemical substances that could degrade its technical properties or cause permanent damage. The shelf life in sealed packaging is 12 months from the production date. The product is covered by warranty, provided that all guidelines specified in the technical data sheet are strictly followed. The manufacturer reserves the right to reject warranty claims in cases where these guidelines have not been observed.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 10/02/2026