

TECHNICAL DATA SHEET

Eurovent **MULTI TUBE**



Highly adhesive, solvent-free multipurpose adhesive, ideal for bonding vapour control layers, roof membranes, and films both indoors and outdoors. It offers excellent ageing resistance, outstanding flexibility and elongation, and is suitable for use in expansion joints, accommodating structural movement. The adhesive is paintable and can be plastered over. Application should take place in a well-ventilated area; once cured (approx. 12–24 hours), any odour will dissipate.

PARAMETER	UNIT	VALUE
Material		Solvent-free acrylic emulsion
Consistency		Pasty
pH value		Alkaline (7,8 – 8,2)
Application temperature	[°C]	-10 to +40
Temperature resistance	[°C]	-20 to + 80
Density	[kg/l]	1,02
Coverage	[mb]	8-10
Cartridge capacity	[g]	620
Color		blue
Packaging	[pcs.]	20
Storage temperature	[°C]	+5°C up to +25°C
Pallet	[pcs.]	720



TECHNICAL DATA SHEET

Eurovent **MULTI TUBE**

Application: For bonding vapour control layers, roof membranes, and films both indoors and outdoors, including expansion joint applications. The adhesive is suitable for plastering and painting over. Application temperature min./max.: -10 °C to +40 °C. Bonding surfaces must be clean, degreased, and absorbent. On weakly bound, dusty, or fibrous substrates, a suitable primer should be used. The applied adhesive layer should be approximately 6 to 8 mm thick. Before curing, the adhesive can be easily removed with water. Once cured, residues can be removed using appropriate cleaning agents by applying them directly to the dried adhesive. Repeat the process as needed until the desired result is achieved. Always ensure that the surfaces being cleaned are resistant to the selected cleaning agent. Application should take place in a well-ventilated area; once cured (approximately 12–24 hours), any odour will dissipate.

Safety: The product must be kept out of reach of children. In case of ingestion or contact with eyes, seek medical advice immediately. Avoid direct contact with skin. Protective gloves and safety goggles are recommended during use.

Storage / transport: The product should be stored at a temperature between +5 °C and +25 °C, in original packaging, in dry, covered, and moisture-free indoor areas. Adhesive packaging may become deformed under heavy load; therefore, stacking with other heavy products is not recommended during transport or storage. The product must be transported in covered vehicles, properly secured against damage. All applicable transport safety regulations must be observed. The product should be protected from contact with chemical substances that may impair its technical properties or cause permanent damage. Shelf life in sealed packaging is 12 months from the date of production.

The product is covered by a warranty only if the instructions specified in the technical data sheet are strictly followed. The manufacturer reserves the right to reject any claims resulting from failure to comply with these guidelines.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 10/02/2026