



PN-EN 13859-2:2010
Declaration of Performance

According to Annex of Regulation (EU) No. 305/2011
Nr DoP 3-1122015-26
for the product

PRIVATE LABEL WALL / Eurovent WALL PROTECT

| | |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Product type: unique identification code of the product type | 3-1122015-26 |
| 2. Intended use or uses of the construction product | Underlay for housewrap or fasade membrane |
| 3. Manufacturer | Eurosystem Polska Sp. z o.o. Sp. K. Wiejska 13, 46-055 Przywory, Poland VAT PL 9372516153 |
| 4. Authorized representative | Not relevant |
| 5. System or systems of assessment and verification of constancy of performance | System 3 i 4 |
| 6. Harmonized specification(s). Notified body(ies). | EN 13859-2:2010 Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 2: Underlays for walls Institut für textile Bau- und Umwelttechnik GmbH Institute for textile building and environment technology Gutenbergstr. 29, 48268 Greven, Germany, identification number: 0799, test report nr 1.1/18493/0017.0.2-2008 |

7. Declared performance

| CHARACTERISTIC | HARMONIZED TECHNICAL SPECIFICATION | VALUES |
|--------------------------------------------------------------------------------------------------------------|------------------------------------|------------------------------|
| Reaction to fire | PN-EN 13859-2:2010 | E |
| Resistance to water penetration | PN-EN 13859-2:2010 | min. W3 |
| Tensile strength MD | PN-EN 13859-2:2010 | ≥240N/50mm (+/- 90N/50mm) |
| Tensile strength CD | PN-EN 13859-2:2010 | ≥160N/50mm (+/- 90N/50mm) |
| Elongation MD | PN-EN 13859-2:2010 | ≤80% |
| Elongation CD | PN-EN 13859-2:2010 | ≤80% |
| Tearing Resistance MD | PN-EN 13859-2:2010 | ≥100 N (+/- 90 N) |
| Tearing Resistance CD | PN-EN 13859-2:2010 | ≥100 N (+/- 90 N) |
| Flexibility at low temperatures | PN-EN 13859-2:2010 | w -30 °C conforming |
| Artificial ageing by long term exposure to the combination of UV radiation and elevated temperature and heat | | |
| Resistance to water penetration | PN-EN 13859-2:2010 | min. W3 |
| Tensile strength MD change | PN-EN 13859-2:2010 | <30% |
| Tensile strength CD change | PN-EN 13859-2:2010 | <30% |
| Elongation MD change | PN-EN 13859-2:2010 | ≤80% |
| Elongation CD change | PN-EN 13859-2:2010 | ≤80% |
| Water vapor transmission | PN-EN 13859-2:2010 | Sd = 0,02 m (+/-0,019 m) |
| Air permeability | PN-EN 13859-2:2010 | <0,06 (m3/m2.h.100Pa) |
| Hazardous substances | PN-EN 13859-2:2010 | Does not contain |

8. The performance of the above stated product is in conformity with the declared performance. This declaration of Performance is issued in accordance with the Regulation (UE) nr 305/2011 under the sole responsibility of the manufacturer specified in this declaration.

Marcin Świerta
President



Przywory, 01.12.2015 r.